




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61F 6/06	A1	(11) International Publication Number: WO 97/30668 (43) International Publication Date: 28 August 1997 (28.08.97)
<p>(21) International Application Number: PCT/GB97/00428</p> <p>(22) International Filing Date: 14 February 1997 (14.02.97)</p> <p>(30) Priority Data: 9603777.5 22 February 1996 (22.02.96) GB</p> <p>(71) Applicant (for all designated States except US): LRC PRODUCTS LTD. [GB/GB]; London International House, Turnford Place, Broxbourne, Hertfordshire EN10 6LN (GB).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): RUDGE, Janette, Mary [GB/GB]; 20 Boyton Close, Haverhill, Suffolk CB9 0DZ (GB). ROGERS, Janette, Louise [GB/GB]; 45 Aldgate, Ketton, Leics PE9 3TD (GB).</p> <p>(74) Agent: LERWILL, John; A.A. Thornton & Co., Northumberland House, 303-306 High Holborn, London WC1V 7LE (GB).</p>	<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU. ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p>	
<p>(54) Title: CONDOMS</p> <p>(57) Abstract</p> <p>A condom has a ring (6) adjacent the open end (1) for expanding the condom to a maximum diameter to maintain the open end outside the vagina, and a tubular portion (3) extending between the ring and the closed end is of a size to form a loose fit around the penis and is formed with a series of circumferential grooves (5), e.g. 3 to 5 grooves around 0.8 cm wide and 1.0 cm deep, so that the condom naturally folds in a bellows like manner for the condom to collapse to a substantially flat condition prior to use.</p> 		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

CONDOMS

This invention relates to condoms and it is especially concerned with condoms which will line the wall of the vagina and, unlike male condoms which are initially donned by the male and fit closely around the penis, are dimensioned to loosely enclose the penis, at least over the length of the condom received within the vagina. For convenience such condoms are referred to herein as "female condoms".

There is currently marketed a female condom consisting of a flexible thin-walled bag-like liner with a closed end and an open end opposite the closed end. The liner is formed from two sheets of plastic material sealed together at their edges, and a solid ring of relatively stiff plastic material is fixed to the liner at the open end and acts to hold the mouth of the liner open. The primary function of the stiff ring is to maintain the open end of the condom outside the vagina. The liner is provided with a second relatively stiff ring which is of smaller diameter than the first ring and is inserted loosely into the liner. This second ring is intended to hold the closed end of the liner in place adjacent the uterus.

The known female condom is not convenient to use and its insertion, particularly due to the need to ensure correct positioning of the loose inner ring, is rather awkward and frequently necessitates an undesirable interruption in the process of sexual activity leading to coitus. Due to the liner being formed from sheet material and the inclusion of the loose ring, the liner has a natural tendency to collapse laterally, which does not facilitate its insertion into the vagina.

The present invention aims to provide a female condom which is more convenient to use without requiring prior application to the penis, and according to the invention there is provided a female condom comprising a closed end and an open end, a ring adjacent to the open end for expanding the condom to a maximum diameter at the location of the ring to maintain the open end outside the vagina, and a tubular wall portion extending between the closed end and the ring, said wall portion being of a size to form a loose fit around the male penis and being formed with a series of circumferential grooves of such a depth that the tubular wall readily folds in a bellows or concertina-like manner whereby the condom collapses longitudinally to a substantially flat condition.

There have been numerous proposals of condoms which are corrugated in some manner, and there have been numerous proposals of condoms with rings or flanges which remain outside the vagina, but the particular combination of a large ring and a grooved wall portion as provided in a condom in accordance with the invention, and which results in an especially convenient and efficacious condom, has not been previously suggested. Furthermore, the condom of the invention is suitable for large scale production by conventional manufacturing processes, whereas the complexities of many of the proposals contained in the prior art would involve manufacturing difficulties making economic production on a commercial scale extremely difficult and in some cases impossible.

The number of grooves included in the tubular wall portion need not be large and very satisfactory results can be obtained with 3 to 5 grooves. Four grooves are currently preferred. Suitably the depth of the grooves is in the range of 0.5 cm to 1.5 cm, and the presently preferred depth is between 0.8 cm and 1.2 cm. In a preferred embodiment, the grooves are formed with intervening circumferential ridges, and the width of the grooves is substantially equal to the width of the ridges e.g. 0.5 cm to 1.0 cm, preferably about 0.8 cm. The grooves

and ridges can be wider, however, such as up to about 1.5cm e.g. around 12 or 13cm and ridges are preferably formed with the bottoms of the grooves and the crests of the ridges substantially semi-circular in cross-section or shaped to merge smoothly with each other to preclude any sharp discontinuities and potential weaknesses along the tubular portion.

The condom of the invention is conveniently manufactured by coating a former with latex or a polymer and allowing the coating material to cure if required before the condom is stripped from the former. The coating can be applied by spraying or by a dip moulding process in which a shaped former is dipped into a liquid bath e.g. of latex, liquid polyurethane, or other polymer composition, and withdrawn carrying with it a thin layer of the coating material. The manufacture by dip moulding may be by multiple dips into the same or successive liquid baths and this can be used to control the thickness of the moulded condom. The former is provided with annular grooves for forming the circumferential grooves of the condom and due to natural flow effects during the dipping process the liquid coating at the bottoms of the grooves can be slightly thicker than on the other surface portions of the former. This may result in the wall thickness of the condom being increased at the bottoms of the grooves e.g. by around 10% to 50%, which can assist the natural tendency for the condom to collapse longitudinally and for the radial undulations to be maintained during the folding process.

The ring adjacent to the open end of the condom is conveniently and preferably integrally formed with the tubular wall. Alternatively the condom may comprise a separately made rubber ring, e.g. a solid silicone rubber ring or a ring formed from rubber tube, which has desirable characteristics of resilient flexibility and can ensure a good level of comfort. The separate ring may be securely attached to the condom wall and can be embedded in the material of the wall by locating the ring onto the former before it is coated with material to form the

condom. Alternatively the ring could be secured to the condom after it has been formed.

In use, a condom in accordance with the invention can be held in its longitudinally collapsed substantially flat form over the vaginal opening, and the closed end of the condom can be pushed into the vagina by the penis as it penetrates the vagina at the beginning of sexual intercourse, the ring which is preferably at least about 7cm in diameter ensuring that the open end remains outside during initial insertion and throughout the coital act.

According to one embodiment of the invention, the female condom includes a second ring of smaller diameter attached to the condom wall a short distance beyond the larger ring. This second ring, which, in accordance with a method known *per se*, can be provided by rolling down a portion of material coated into the former before it is fully cured, is dimensioned to have a close fit around the penis so that when the penis is withdrawn it removes the condom from the vagina.

Female condoms embodying the invention are more convenient to use than those currently available.

To facilitate a clear understanding of the invention some particular embodiments will now be described with reference to the accompanying drawings, in which:-

Figure 1 is a side view of a female condom embodying the invention;

Figure 2 is a plan view of the condom shown in Figure 1;

Figure 3 is a side elevation of a former used to manufacture the condom of Figures 1 and 2;

Figure 4 shows the condom in its flat folded condition;

Figure 5 is a side view of a second female condom according to the invention;

Figure 6 is a plan view of the condom shown in Figure 5;

Figure 7 is a side elevation of a former used to manufacture the condom of Figures 1 and 6; and

Figures 8 and 9 show in side elevation two modified formers suitable for manufacturing condoms generally similar to that of Figures 1 and 2.

The female condom illustrated in Figures 1, 2 and 4 is formed of latex or polyurethane by a dip moulding process using the former of Figure 3. The condom has an open end 1, a closed end 2 and a tubular wall 3 interconnecting the ends and formed with radial undulations defined by alternate circumferential ridges 4 and grooves 5. At the open end 1 the condom is provided with a relatively stiff but flexible ring 6 which may be silicone rubber or made of tubular rubber, but can be conveniently formed integrally with the tubular wall. The ring has a diameter of about 7 cm and it radially expands the condom to a maximum diameter. The former includes an upper moulding portion 12 of cylindrical form and having a diameter approximately equal to that of the condom ring 6. At its lower end the former has a substantially hemispherical dome-shaped portion 13 for forming the closed end wall 2 of the condom. Between the portions 12 and 13 are a series of annular ridges 14 which define annular grooves 15 for forming the ridges 4 and grooves 5 of the condom, respectively. The crests of the ridges 14 and the bottoms of the radial grooves 15 are substantially semi-circular in cross-section and the grooves are about 1.0 cm deep and 0.8 cm wide. The former is dipped into a bath of e.g. liquid latex and becomes coated to a level a little below the upper edge of the portion 12. The thickness of material coating the bottoms of the grooves is typically 0.04 to 0.10 mm compared with a thickness of 0.02 to 0.06 mm at the ridge tops, although the thickness may be up to 0.12 mm at the grooves and up to 0.1 mm at the ridges. After curing sufficiently, some of the material coating the portion 12 is rolled down from its upper edge to form a bead which becomes the ring 6 of the condom. If required

additional bead material could be applied over the part of the dipped material to be rolled to form the bead. When the latex is cured, the condom is stripped from the former, and after appropriate testing it is collapsed longitudinally to the flat condition shown in Figure 4, which is readily achieved since the condom has a natural tendency to fold in a bellows-like manner due to the grooves 4. The condom is then packaged. When it is to be used, it is removed from the package and held in the flat condition over the vagina to be inserted as previously described.

The condom of Figures 5 and 6 and the former of Figure 7 are for the most part the same as those described above and only the modifications will be described. The condom has a large ring 26 and beyond it at the open end a smaller ring 27 having a diameter about half that of the large ring. The former has an upper portion with a cylindrical section 32 located between frusto-conical sections 33, 34 and a neck portion 35 above the upper frusto-conical section 33. When provided with a dipped coating, the material coating the neck portion 35 is rolled down from its upper edge to form a bead which constitutes the smaller ring 27 of the condom. After the condom has been stripped from the former, a separate solid rubber ring is inserted to provide the larger ring 26. If preferred the rubber ring can be located onto the cylindrical section 32 of the former before it is coated so that the ring becomes embedded in the condom material during the dip moulding process.

The condom is used in essentially the same way as the first embodiment. However, when used to insert the condom into the vagina the penis is passed through the small ring 27 as well as the larger ring 26 which always remains outside the vagina. When the penis is subsequently withdrawn, as it is gripped lightly by the ring 27, the condom will be simultaneously withdrawn from the vagina.

Although the condoms described herein have for convenience been

referred as "female condoms", it should be understood that this term has been used only to mean that the portion of the condom between the closed end and the expansion ring will be a loose fit around the penis, and if preferred by users, there is no reason why the condom should not be placed over the penis of the male before insertion into the vagina of the female.

The formers of Figures 8 and 9 are particularly suited to the manufacture of condoms as shown in Figures 1 and 2 and having integral rings at their open ends. Above the lower grooved section each former has a substantially uniform cylindrical shape with a diameter of about 7cm. This cylindrical portion can be coated with material which is rolled up from its free edge before the material had dried or cured in order to form the integral ring. In the former of Figure 8 the bottoms of the annular grooves 15 have a radius of curvature of about 6 mm and the crests of the annular ridges 14 between the grooves have a similar radius of curvature. The diameter of the former at the bottoms of the grooves is about 41 mm and at the crests of the ridges the diameter is about 65 mm, the depth of the grooves being about 12 mm. The width of the ridges and of the grooves, measured at half the depth of the grooves where the curvature changes from concave to convex, is 12 mm. In the former of Figure 9, the grooves 15 are shallower, the diameter of the former at the bottoms of the grooves 15 being 50 mm and the diameter at the crests of the ridges 14 being 65 mm so the groove depth is 7.5 mm. The radius of curvature at the bottoms of the grooves and at the crests of the ridges is 7 mm. The edge profile of the grooved section of the former is more sinusoidal than with the formers of the previous embodiments. The width of the ridges and the grooves, again measured at half the groove depth where the curvature changes from concave to convex is about 13 mm. The formers of Figures 8 and 9 have small nipples 45 at the centre of the lowermost dome-shaped portions 13 for producing shallow pockets at the closed ends of the condoms produced on these formers.

It will be appreciated that the condoms moulded on the formers of Figures 8 and 9 will have dimensions which are essentially the same as those of the formers.

CLAIMS:

1. A condom, comprising a closed end (2) and an open end (1), a ring (6) adjacent the open end for expanding the condom to a maximum diameter at the location of the ring, to maintain the open end outside the vagina during sexual intercourse, and a tubular wall portion (3) extending between the closed end and the ring, said tubular wall portion being of a size to form a loose fit around the penis, characterised in that the tubular wall portion (3) is formed with a series of circumferential grooves (5) of such a depth that the tubular wall (3) readily folds in a bellows or concertina-like manner for the condom to collapse longitudinally to a substantially flat condition.

2. A condom according to claim 1 wherein the grooves (5) are 3 to 5 in number

3. A condom according to claim 1 or 2, wherein circumferential ridges (4) are located between the grooves, the ridges and grooves being provided over substantially the entire length of the tubular portion.

4. A condom according to claim 3, wherein the width of the grooves (5) is substantially equal to the width of the ridges

5. A condom according to claim 3 or 4 wherein the bottoms of the grooves (5) and the crests of the ridges (4) are substantially semi-circular in cross-section

6. A condom according to any one of claims 1 to 5, wherein the width of the grooves (5) is in the range of 0.5 to 1.5 cm.

7 A condom according to any one of claims 1 to 6, wherein the depth of the grooves (5) is in the range of 0.5 to 1.5cm.

8 A condom according to any one of claims 1 to 6, wherein the depth of the grooves is in the range of 0.8 to 1.2cm

9 A condom according to any one of claims 1 to 8, wherein the wall thickness at the bottom of the grooves (5) is greater than the wall thickness of the tubular wall portion between the bottoms of the grooves.

10 A condom according to any one of claims 1 to 9, wherein at least the tubular portion (3) of the condom is formed by dip moulding.

11 A condom according to claim 10, wherein the ring (6) is formed by rolling up material coated onto a former on which the tubular portion of the condom is formed.

12 A condom according to any one of claims 1 to 10, wherein a second ring (27) of smaller diameter than the expansion ring (26) is located at the open end of the condom

13 A condom according to claim 12, wherein the diameter of the smaller ring (27) is approximately half that of the expansion ring (26).

14 A condom according to any one of claims 1 to 13, wherein the expansion ring expands the condom to a maximum diameter of at least about 7 cm

1/4




Fig.1




Fig.2




Fig.4

2/4




Fig. 3




Fig. 7

3/4




Fig. 5




Fig. 6

4/4




Fig. 8




Fig. 9

INTERNATIONAL SEARCH REPORT

Int. Appl. No.
PCT/GB 97/00428

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A61F6/06

According to International Patent Classification (IPC) or to both national classification and IPC.

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 966 166 A (LEFFLER JOHN T) 30 October 1990	1-11
Y	see page 2, line 57 - page 3, line 44; figures 1-3	12-14
X	GB 2 266 244 A (FERGUS THOMAS) 27 October 1993 see claim 1; figure	1
Y	US 4 798 600 A (MEADOWS MICHAEL E) 17 January 1989 see figure 1	12-14
A	US 5 269 320 A (HUNNICUTT JANE) 14 December 1993	
A	US 4 862 901 A (GREEN IVAN L) 5 September 1989	

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *&* document member of the same patent family

Date of the actual completion of the international search

27 May 1997

Date of mailing of the international search report

-4.06.97

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+ 31-70) 340-3016

Authorized officer

Sánchez y Sánchez, J

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/GB 97/00428

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4966166 A	30-10-90	NONE	
GB 2266244 A	27-10-93	AU 646553 B	24-02-94
		CA 2084903 A	10-06-94
		NZ 250059 A	26-09-95
		AU 1491492 A	18-11-93
		US 5398699 A	21-03-95
US 4798600 A	17-01-89	NONE	
US 5269320 A	14-12-93	NONE	
US 4862901 A	05-09-89	NONE	